

1175 Series Foam Seals

Floor to Floor
Floor to Wall



Movement Rating $\pm 50\%$

Product Guide



- ▶ Developed to meet DOT performance requirements for vehicular loading while offering 100% shear movement.
- ▶ Foam seals create a water tight, insulated seal.
- ▶ Seal material is UV stable, and resistant to solvents and fuels which are commonly found in parking garages, and other roadway surfaces.
- ▶ Capable of handling vertical and horizontal joint movement.
- ▶ Open cell foam is constantly self-expanding, allowing systems to maintain a watertight seal while undergoing rapid joint movement.
- ▶ Allows for 100% movement ($\pm 50\%$)
- ▶ 1175 foam seal comes pre-compressed in 5'-0" [1.5mm] lengths for ease of installation.
- ▶ Foam seal is permanently adhered to joint edge using a strong, 2 part epoxy (JPR013).
- ▶ Standard Color: Gray.
- ▶ For joint widths larger than 3" (76mm) in horizontal applications, JointMaster recommends a coverplate over the 1175 Foam Seal.

Application	System	Joint Width		Seal Height		Movement \pm	
		US	mm	US	mm	Compression/Expansion	
		US	mm	US	mm	US	mm
1175 Floor/Floor Floor/Wall	1175-050	1/2"	13	1 1/2"	38	1/4"	6
	1175-100	1"	25	2"	51	1/2"	13
	1175-200	2"	51	3"	51	1"	25
	1175-300	3"	76	3"	76	1 1/2"	38
	1175-400	4"	102	3"	76	2"	51
	1175-500	5"	127	3"	76	2 1/2"	64
	1175-600	6"	152	4"	102	3"	76
	1175-700	7"	178	4"	102	3 1/2"	89

1175 series available in 1/2" size increments up to 7" in width, contact your InPro Rep. for more info

IPC.1569/REV.12

1175 Series

Foam Seals

1175 Series Floor/Floor
(2" (50mm) system shown)

