



Inpro Bond Mastic Construction Adhesive Technical Data Sheet

TYPE OF ADHESIVE:

Aqueous construction adhesive

TECHNICAL DATA:

Viscosity: Over 300,000 CPS. @76F Brookfield RVT#7/2 RPM
pH: 5.0 ± 1
Density: 1.05 ± .05
Solids: 61% ± 2%
Color: White
Freeze/Thaw: 5 cycles

PROPERTIES:

InProBond Adhesive is a water based pressure sensitive adhesive designed for wallcovering applications. This product exhibits very aggressive tack and good freeze-thaw stability. InProBond should be applied evenly on substrates with a notched trowel. Application instructions must be followed. This product is environmentally friendly.

HANDLING AND APPLICATION:

Supplied ready for use. Freeze thaw stable.

Application is dependent on humidity and air temperature. Carefully read and understand application instructions. Clean up with warm water when wet. When dry, clean up with InProClean Vinyl Cleaner or mineral spirits.

Meets FDA Section 21 CFR 175- 105 for indirect food contact.

PRECAUTIONS:

Do not mix with other adhesives.

PACKAGING:

5 gallon and 1 gallon pails

STORAGE CONDITIONS:

Rotate stock, use oldest first.

1 year in unopened container stored in cool dry environment

Keep covered to prevent moisture loss and contamination